

THE HYDR8 WATER PURIFICATION PROCESS



WATER

5



FILTER



FILTER



FILTER



BOOSTTM











TOUCHLESS SENSOR-ACTIVATED WATER **PURIFICATION**

SYSTEM



SEDIMENT FILTER

REDUCES PARTICLES SUCH AS DIRT, SILT, PIPE RUST

PRE-CARBON FILTER

REDUCES CHLORINE, CHEMICALS AND PESTICIDES

LEAD & CYST FILTER

CAPTURES CONTAMINANTS SUCH AS DISSOLVED SOLIDS, ARSENIC, LEAD, PHARMACEUTICALS, AND METALS

INVIGOR8 BOOST™ MINERAL ALKALINE FILTER (OPTIONAL)

ADDS ELECTROLYTES SUCH AS POTASSIUM, SODIUM, **CALCIUM & MAGNESIUM NATURALLY INCREASING THE**

ALKALINITY OF THE WATER

ACTIVATED OXYGEN INJECTION

O3 STERILIZES THE HOLDING TANK AFTER 8 HOURS OF NONUSE

Our systems are tested and certified to the highest industry standards for safety and performance. The 4i is certified by IAPMO in accordance with ANSI/NSF 372 for lead free products and certified by IAPMO R&T in accordance with UL 399 and CSA 22.2 for electrical safety.



Touchless Sensor Activation

Hygienic, touchfree operation.



Anti-Microbial Surface

Anti-microbial additive maintains cleanliness of unit exterior.



High-Capacity Drip Tray

Optional drain connection prevents need for emptying.



11.7"W x 19.5"D x 17.8"H

SPECIFICATIONS



Advanced **Purification** Technology

Proprietary, multistage, reverse osmosis process is certified to industry standards.



Activated Oxygen Self-Cleaning

Advanced technology circulates water and cleans tanks and lines to maintain water freshness.



Countertop

Option Now

Available!

74/7 System **Monitoring**

Continuous monitoring of system performance and water quality with real-time status displayed on LCD screen and bluetooth compatible service арр.



Large LCD screen displays real-time system performance and water quality status.

High-end glass front panel

Touch-free sensor activation

Hot water safety lock

Color-changing indicator light for precise dispensing

Large drip tray

High-capacity cold tank

Dent-resistant steel frame

- ► DIMENSIONS
- 50.9" H X 14" W X 17" L (1293MM H X 355.6MM W X 431.8MM L)
- ► COLD TANK CAPACITY **3 GALLONS**
- ► HOT TANK CAPACITY (2 LITERS)
- ► DISPENSE AREA 12" TALL (305MM)
- ► RECOMMENDED WATER PRESSURE 60-70 PSI
- ► RATED VOLTAGE/FREQUENCY 120V/60HZ 220V/50HZ
- ► POWER CONSUMPTION 120V/60HZ 220V/50HZ
- ► WEIGHT 69.9 LBS (31.7 KGS)



GET YOUR QUOTE TODAY! CALL US NOW:

